

09/784,778

14122

In the Specification:**Insert the following paragraph on Page 1, line 2:****CROSS-REFERENCE TO RELATED APPLICATION**

B2
The contents and disclosure of my Application Serial No. 09/784,776, contemporaneously filed February 15, 2001, for "Decorative Light Plug" is incorporated herein by reference.

Replace paragraph beginning on page 4, line 13 to page 5, line 5 with:

B3
With reference to Fig. 1, the collar (3) has a through hole (31) defined to allow the extension of the second cover (22) and has an inner thread (32) formed to correspond to the thread (221) on the second cover (22) of another decorative light, such that the collar (3) is able to screw onto the second cover (22) of another decorative light. It is noted that the axial depth of the thread (221) on the second cover (22) is only half of the axial depth of the inner threading (32) of the collar (3) and the collar is slidably movable on the decorative light. To prevent the collar from detachment from the decorative light, the first adapter (1) has a flange (121), as shown in Figs. 1 and 2, formed on an outer periphery of the first cover (12). The inner diameter of the collar (3) is large than that of the first cover (12), such that a gap (not numbered) is defined between the first cover (12) and the collar (3). Therefore, when the user wants to extend the total length of the decorative light, the user may use the first adapter (1) of one decorative light to connect to the second cover adapter (2) of another decorative light. After the extended prongs (212) of the male connector (21) are inserted into the corresponding second plated hole (112) of the first adapter (1), the collar (3) is able to screw onto the outer thread (221) of another decorative light so that the total length of the decorative light is lengthened.